

ENGLISH



FR-PL100M

LED spotlight for indoor and outdoor use, equipped with SMD LEDs type .

Its construction allows you to select the color temperature of the light emitted between 3,000 / 4,000 / 5,700 ° K, simply by acting on the selector placed in the rear side, even with the spotlight switched on and the spotlight already installed.

This feature allows you to adapt the color temperature to that of the surrounding environment for perfect integration.



Compact

The light and compact system allows for absolute ease of installation. The shell has a minimum thickness of only 39 mm. The fixing bracket is sized to optimize space during installation.

Elegant

Glossy finish, neutral white body and anti-reflective and unbreakable satin glass. Make it a design object, elegant in any environment in which it is placed. The ventilation slots give the sight a light and low impact look.

Efficient

Designed and built in compliance with the strict EU eco-design regulations. The result is an extremely efficient system, with a very high lighting capacity for the same power used. Designed to last over time to solve the problems of WEEE disposal.

ENGLISH



FR-PL100M

ITEM CODE
EAN CODE
TECNOLOGY

FR-PL100M
8033971217186
LED SMD

DIMENSIONS

length
width
height
net weight

225 mm
325 mm
39 mm
1,674 kg

TECHNICAL SPECIFICATIONS

power
equivalent power
brightness
light color
light beam
color rendering (CRI)
dimmable
working voltage
power factor (pf)
frequency
flickering
LED life span
ignition cycles
working temperature
insulation class
protection degree
power cable
packing pcs

100 w
1.000 w traditional source
10.000 lm
3.000 / 4.000 / 5.700 °K
120°
80
NO
185-265 AC
0,95
50/60 Hz
<0,1
36.000 Hr
15.000
-40 ~ +50 °C
II
IP65
PVC lenght 150cm
5 individually packed



FRIGGERI

KKK 3.000 °K
4.000 °K
5.700 °K
TECHNOLOGY

100_W

equivalente a
1.000w alogeno
equivalent to
1.000w halogen

CE IP65

**SELECTABLE
COLOR
TEMPERATURE**

